



VENESTA DEBOBINADA BLANCA



El terciado decorativo es un producto ligero, versátil y resistente que, gracias a su amplia variedad de especies y a su formato, ofrece excelentes posibilidades para quienes buscan acabados de gran belleza y finas terminaciones.



USOS Y APLICACIONES

Estanterías
Instrumentos musicales
Accesorios y maquetas
Juguetes
Revestimientos para cielos rasos y paredes
En la industria de la madera, también es muy valorado para el acabado de muebles, puertas y mamparas funcionales



CARACTERISTICAS

El terciado decorativo (venesta) se fabrica con láminas de madera natural unidas con adhesivos sintéticos y fibras dispuestas perpendicularmente, lo que le da mayor resistencia que la madera maciza.

Ofrece solidez, estabilidad dimensional, aislamiento térmico y acústico, resistencia al fuego y a la humedad, y buen desempeño en climas variables.



ALMACENAMIENTO

Se recomienda almacenar los tableros en un lugar seco, ventilado y protegido del sol y la humedad. Deben apilarse horizontalmente sobre una base firme con separadores. Evitar rayaduras al manipularlos. Si hay riesgo de polvo o salpicaduras, cubrir con plástico o lona liviana, asegurando ventilación. También deben evitarse cambios bruscos de temperatura y humedad, que pueden causar hinchamiento o delaminación.



ESPECIFICACIONES TECNICAS

Dimensiones estándar: 2440 x 1220mm.
Espesores Disponibles: 3, 4mm.
Composición: Chapas delgadas de madera unidas con adhesivo
Resistencia a la Humedad: Bajo
Acabado Superficial: Lijado
Color: Natural
Adhesivo Usado: Urea-Formaldehído

CUADRO PRUEBAS FISICOMECAICAS

NOMBRE	TIPOLOGIA	Espesor (mm)	DIF. ESPESOR	DENSIDAD KG/M ³	RESISTENCIA FLEXION
					MOR KG/CM ²
VENESTA	RUSTICO	3	±3 mm	419,22	326,19
VENESTA	RUSTICO	4	±3 mm	467	531,49



WHITE ROTARY-CUT VENEER PLYWOOD



White rotary-cut veneer plywood is a lightweight, versatile, and durable decorative panel. Thanks to its thin format and natural finish, it offers quality aesthetic solutions for a wide range of applications. Its multilayer structure provides dimensional stability, mechanical strength, and a suitable surface for high-precision finishes.



TECHNICAL SPECIFICATIONS

Standard Dimensions: 2440 x 1220 mm

Available Thicknesses: 3 mm. 4 mm.

Composition: Thin wood veneers bonded with adhesive.

Moisture Resistance: Low

Surface Finish: Sanded

Color: Depending on species

Adhesive Used: Urea-Formaldehdev



USES AND APPLICATIONS

Lightweight shelving
Musical instruments
Models, accessories, and toys
Decorative ceiling and wall paneling
Furniture finishes, doors, and functional partitions



FEATURES

Decorative plywood (venesta) is made from natural wood veneers bonded with synthetic adhesives, with cross-oriented fibers that provide greater strength than solid wood.

It offers strength, dimensional stability, thermal and acoustic insulation, resistance to fire and moisture, and reliable performance under variable climate conditions.



STORAGE

It is recommended to store the boards in a dry, ventilated place, protected from sunlight and moisture. They should be stacked horizontally on a firm base with spacers. Avoid scratches during handling. If there is a risk of dust or splashes, cover them with plastic or a light tarp, ensuring proper ventilation. Sudden changes in temperature and humidity should also be avoided, as they may cause swelling or delamination.

PHYSICAL AND MECHANICAL TEST TABLE

NAME	TIPOLOGY	Thickness (mm)	DIFF THICKENSS	DENSITY KG/CM³	FLEXURAL RESISTANCE
					MOR KG/CM²
PLYWOOD	RAW	3	±3 mm	419,22	326,19
PLYWOOD	RAW	4	±3 mm	467	531,49